

Warranty

24
Months

Included



Battery

Included



Calibration tool

Included



Offset-Accur

Included



RS 232C

optional



PC Software

Technical Highlights:

- External Sensor
- Accuracy:
 - **Standard: 3 %** of the measured value
 - **Offset-Accur: 1 %** of the measured value



Delivered in a
hard carrying
case

Offset-Accur: This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration (base plate and calibration foils).
This results in a superior accuracy of approx. 1 % of the measured value.

Size: L 124 x B 62 x H 30 mm;
Weight: 200 g

Power supply 4 x 1.5V AAA Battery

External sensor for better access to the test object (Cable length: 1 m)

Auto-Power-Off function

Min measuring area: 5 mm
Min base thickness: 0.3 mm

Selectable **measuring units:** metric, imperial

Base plate and calibration foils included

Resolution of TD F and N models: 0,1 µm < 100 µm;
1 µm > 100 µm

Data Output to PC

- RS 232C Output included
- Option: PC Software and cable to PC
- ATD-01**

Model	Test Objects	Min. radius workpiece	Max	Resolu- tion	ISO Calibration Certificate
TD 1250-0.1 F	Non-magnet coatings on steel and other metals	Convex: 1.5 mm Concave: 25 mm	1 250 µm	0,1 µm	CT 2000
TD 1250-0.1 N	Insulation coatings on non-ferrous metals	Convex: 3 mm Concave: 50 mm	1 250 µm	0,1 µm	CT 2000
TD 1250-0.1 FN	Combination Instrument combining F and N	As F or N	1 250 µm	0,1 µm	CT 2000

